

DOOR TO VANITY

EYES FOR THE JOB- EPISODE 308.2

'RECLAIM TO FAME'



MATERIALS NEEDED

- One sheet of 1/4" x 2' x 4' mdf
- Five pieces of 2x10x36" pine
- One 22"x12" mirror
- Four pieces of 1x2x12' pine
- Twelve pieces of 2 x 2 pine
- One Litre of paint
- One LED Lighting Strip - 3 m
- One Lead paint test kit
- Four 7"x7" brackets
- Two 24"x15" brackets
- Door
- Chalkboard paint
- 1" Screws

TOOLS NEEDED

Palm Sander
Sandpaper 100 grit
Screw Gun
Screws
Chop Saw



STEP BY STEP BUILD PLAN

1. Test the door paint for lead. If lead is present skip the sanding step and instead give it a new coat of paint to seal in the lead that is present.
2. If no lead is present, begin by sanding the door, with a palm sander/sandpaper using 100 grit.
3. Paint the door, and let it stand until dry.
4. While the paint is drying, you can begin preparing the shelves.
 - a. Cut 5 pieces of 1 3/8" x 12" x 4' at 32", for the shelves, and desktop. Rip three of these to 8" for the shelves.
5. For the Vanity Table Top
 - a. Cut 2 pieces of 1 3/8" x 12" x 48" to 32", combine with glue and secure with pocket hole screws. Rip to 16".
6. Preparation/Shelving Unites
 - a. Lay the door down on its back.
 - b. Starting from top down, mark at 6".
 - c. Then mark 18".
 - d. Then mark 30".

- e. And mark for the vanity at 52".
- 7. Installing Of Shelving units
 - a. Paint mdf with chalkboard paint and install above the line for vanity brackets.
 - b. Install brackets below each set of lines.
 - c. Install shelves on each set of brackets
- 8. Vanity Back Piece
 - a. Paint 33" x 23" backing,
 - b. Fold material pieces one side at a time, and staple into wood. Ensuring tight and snug. Repeat for other panel.
 - c. Fix mirror to centre of 24" x 32" painted panel.
- 9. Take completed Vanity Panel, and install above vanity table top, using 3 screws per side.
- 10. For added aesthetic, consider installing string lights to underside of bottom shelf, to enhance lighting of vanity table top, and mirror.